## BATAAN PENINSULA STATE UNIVERSITY

Balanga City, Bataan

## OFFICIAL BIDDING FORM

em lo.	QTY	Unit	SPECIFICATIONS	OFFER; (Brand)	Unit Cost	Total Cost
1	1	lot	LOT A - Data Center		Total ABC- LOT A	8,470,030.00
	1		Firewall utm machine with bandwidth manager, web and Application filtering		LOTA	
	2	units	Servers CPU 2*Intel Xeon Silver 4210R 2.4G, 10C/20T, 128G (32G*4) Memory, 8*3.5in disk slots, 1*128G OS disk, 6*GE+2*10GE, no cache disk or data disk. LC-LC, Multi mode, 3 meters. SFP+ 10GE Multimode Optical Transceiver, for short distance transmission (850nm, 300M). 2TB 7200RPM 3.5" SATA HDD(Enterprise). 960GB SSD Intel S4600 3D NAND TLCSSD 2.5", SATA 3.0 6Gbps,			
	2	unit	Server virtualization, HA, DRS, Automated Hot Add, backup, clone, network virtualization, Distributed Firewall, Drawable topology, visualized network, switch, router, with Storage virtualization, 2-3 copies, SSD read and write acceleration, data localitv. Striping. With Technical Support 7x24 UPS 1000VA, 230V Output (Rack-Mounted) runs with an operating voltage range of 180 to 287 V. has maintenance free sealed lead acid battery with suspended electrolyte battery type-BX1200MI-MS APC Back GR11-1kva/900w rackmount online unit w/ railkitGR11-1kva			
	1	unit	Power Distribution Unit (6u) 19" Rack Mount, specially designed for 19" Cabinets			
	1	unit	47U 600*800*2276mm "4 fans, 2 shelves, 1 vertical cable manager, 1 US 16 ways PDU, single/double open rear door open rear door" 7.46 feet			
	20	unit	Desktop Core i3-10100, 8GG RAM, 1TB HDD Win10 Home, Bundled with Monitor 23.8, mouse, keyboard &			
	4	unit	Structured Cabling (FOC Installation) Switches 24 port and transceiver 10G SFP+ Fiber Transceiver (Multi mode)			
	2	unit	L2+ 24-Port 10/100/1000T + 4-Port, 10G SFP+ Stackable Managed Switch (Hardware Layer3 IPv4/IPv6 Static Routing, ERPS Ring, hardware stacking up to 6 units, IP clustering up to 16 units)			
	15	boxes	Cat 6 cable, blue (305m)			
	800	meters	Fiber Optic Cable (aerial, 4 core single mode fiber)-OUTDOOR STEEL ARMOURED FIBER OPTIC CABLE-OM2 type FOC			
	850	pcs	PVC Electrical pipe, 15mm (½"/1"/2" dia., PLASTIC) and accessories			
	60	pcs	Cat6 Patch cable, blue, 2 meter -Belden Cat6 Patchcord			
	60	pcs	Keystone Jack CAT6			
	8	unit	Power Distribution Unit (6u)			
	42	pcs	Surface box metal			
	8	unit	1G SFP LC LX Optical Transceiver, must compatible with the existing network devices at ISI-1000BASE-SX SFP Transceiver, Single Mode Installation Services for fiber optic cable, CAT6 cable, pipes			
	1		faceplate/surfacebox, UPS and grounding, wireless access- point, patch panel, keystones, power distribution unit, grounding, close- rack cabinet LOT B - Learning Management		Total ABC	
			System		Total ABC- LOT B	13,080,000.00

units  units  Integration Hardware capable of having Interactive Functions at any little display panel and projector used for limited face to face classes. Similar classipal panel and projector used for limited face to face classes. Similar classipal panel and projector used for limited face to face classes. Similar classification of the face of face classes. Processor: Intel Core IS, 8th Gen, Graphics. UHD Graphic, Support 46, 860Hz. Refrask Rais, AMMemory: 4GB, Churchell Cores.  Thinker View Camera Full Ho Camera with 110 Decree FOV, and built-in mic Array Wireless Prosenter System with Lavaller Microphone  LOT C: Live Streaming and Recording System  Modia Recorder Box An all-in-one solution with 7-inch touch screen. It is for live streaming& recording synchronically. Support inputs are Holff device, Str. 1857 protocol (Peramera, H.264 decorder) recorded files and more mini HD max Sin Interactive Display OPS PC module Processor: Intel Core IS, 8th Gen, Graphics: UHD Graphic, Support 4k@60Hz Refresh Rate, RAMMemor: 4GB Mobile Rack for 60-100 Tracking Camera 12 1(28-inch-high quality CMOS sensor. Resolution up to 1920/c1056) 11 Tipod System Kit Twe-stage aluminum tripod with 60mm bowl. Supports loads up to 11 to 15. Red panifit drag with independent panifit locks VP-CKB Keyboard controller for PTZ, conference and surveillance camera. With 4D stick, password protected 11 Pull function raystem keyboard controller for PTZ, conference and surveillance camera. With 4D stick, password protected 11 Pull function raystem keyboard controller for PTZ, conference and surveillance camera. With 4D stick, password protected 12 Port Glagolit Ummanged Desktop Switch School Conference (TX 1650T) with 4 GB GDDR6 memory with burndled momotiner music keyboard and AVR Wireless Prosenter System with Lavaller Microphone S-port Glagolit Ummanged Desktop Switch School Converter, HDMI (emale) to Display Port 1 Backdrop Setup Converter, HDMI (emale) to Display Port 2 Genetrs 3,5mm XLR Female 5 meters RG6 Coaxial Cable with BINC Connector	
tace classes. S5" interactive display OPS PC module Processor: Intel Core IS, 8th Gen, Graphics; UHD Graphic, Support 4k@60Hz Refresh Rate, AMMemory: 4GB, It is for live with 110 Degree FOV, and built-lin mic Array Wireless Presenter System with Lavalier Microphone  LOT C: Live Streaming and Recording System  Media Recorder Box An all-in-one solution with 7-inch touch screen. It is for live streaming frecording synchronically. Support injuts are HDMI devices, RTSP protocol (IP camera, H.264 decoden, recorded files and more mini HDM max 65" Interactive Display OPS PC module Processor: Intel Core is, Sth Gen, Graphics: UHD Graphic, Support 4k@60Hz Refresh Rate, RAMMemory: 4GB Mobile Rack for 60-100 Tracking Camera 1/2 &inch-high quality CMOS sensor. Resolution up to 1920x 1690 1920x 1690 1 Tropost System Kil Two-stage aluminum tripod with 60mm bowl, Supports loads up to 11 lb. Fixed anorith drea with independent pant/lit locks VP-CMS Reviboard Controller for PTZ, conference and surveillance camera, With 4D stick, password protected HDMI Capture Box Max input resolution 1920x 1200, with USB, 1HDMI, embedded audio Streaming PC 5.6" display with IPS and Full HD 1920x 1080 resolution, supporting 144Hz N/IDIA GeForce GTX 1850Ti with 4 GB GDDR6 memory with bundent monitor mursue, kenhandra and AUP. Wireless Presenter System with Lavalier Microphone 5-Port Gigabit Ummanagad Desktop Switch 880 LED Bulb Panel 3200-5600K with 78.7 Inches Stand Lubrition Kit 1 High Speed HDMI* Cabbe with Ethemet10.70m (28f1)K@60Hz (4:2.0) "Interactive Display to AV Mixer/Media Box High Speed HDMI* Cabbe with Ethemet10.70m (28f1)K@60Hz (4:2.0) "Interactive Display to AV Mixer/Media Box High Speed HDMI* Cabbe with Ethemet10.70m (38f1)K@60Hz (4:2.0) "Interactive Display to AV Mixer/Media Box High Speed HDMI* Cabbe Sub GA Sub Sub Box Ava Sub Setup Setup Cabbe Sub GA S	
LOT C: Live Streaming and Recording System    Media Recorder Box	
Media Recorder Box   An all-in-one solution with 7-inch touch screen.	
Media Recorder Box An all-in-one solution with 7-inch touch screen. It is for live streaming& recording synchronically. Support inputs are HDMI devices, RTSP protocol (IP camera, H.264 discoder). recorded files and more mini HD max 65' interactive Display OPS PC module Processor: Intel Core IS, 8th Gen, Graphics: UHD Graphic, Support 4k@60Hz Refresh Rate, RAM/Memorv: 4GB Mobile Rack for 60-100 Tracking Camera 1/2.8-inch-high quality CMOS sensor. Resolution up to 1920x1080 Tripod System Kit Two-stage aluminum tripod with 60mm bowl, Supports loads up to 11 ib. Fixed pan/filt drag with independent pan/filt locks VP-CKB Keyboard Controller Full function system keyboard controller for PTZ, conference and surveillance camera. With 4D stick, password protected HDMI Capture Box Max input resolution 1920x1200, with USB, 1HDMI, embedded audio Streaming PC 5.6' display with IPS and Full HD 1920 x 1080 resolution, supporting 144Hz NVIDIA GeForce GTX 1650Ti with 4 GB GDDR6 memory with bundled monitor. mouse. kewboard and AVR Wireless Presenter System with Lavalier Microphone 5-Port Gigabit Unmanaged Desktop Switch 660 LED Bulb Panel 3200-5600K with 7.8.7 Inches Stand Lighting Kit High Speed HDMI™ Cable with Ethernet7.60m (25th)4K@60Hz (4:2:0) **Camera to AV Mixer/Media Box High-Speed HDMI™ Cable with Ethernet10.70m (35th)4K@60Hz (4:2:0) **Camera to AV Mixer/Media Box High-Speed HDMI™ Cable with Ethernet10.70m (35th)4K@60Hz (2:20) **Interactive Display to AV Mixer/Media Box High-Speed HDMI™ Cable with Ethernet10.70m (35th)4K@60Hz (4:2:0) **Camera to AV Mixer/Media Box High-Speed HDMI™ Cable with Ethernet10.70m (35th)4K@60Hz (4:2:0) **Camera to AV Mixer/Media Box High-Speed HDMI™ Cable with Ethernet10.70m (35th)4K@60Hz (4:2:0) **Theractive Display to AV Mixer/Media Box High-Speed HDMI™ Cable with Ethernet10.70m (35th)4K@60Hz (4:2:0) **Theractive Display to AV Mixer/Media Box High-Speed HDMI™ Cable with Ethernet10.70m Standard Box to HDMI Capture Box Backdrop Setup  Converter, HDMI (female) to Display Port S meters RG6 Caaxia	79,000.0
66" Interactive Display OPS PC module Processor: Intel Core i5, 8th Gen, Graphics: UHD Graphic, Support 4k@60Hz Refresh Rate, RAMMemorv: 4GB Mobile Rack for 60-100 Tracking Camera 1/2.8-inch-high quality CMOS sensor. Resolution up to 1920x1080 Tripod System Kit Two-stage aluminum tripod with 60mm bowl, Supports loads up to 11 lb. Fixed pan/tilt draq with independent pan/tilt locks VP-CKB Keyboard Controller Full function system keyboard controller for PTZ, conference and surveillance camera. With 4D stick, password protected HDMI Capture Box Max input resolution 1920x1200, with USB, 1HDMI, embedded audio Streaming PC 5.6" display with IPS and Full HD 1920 x 1080 resolution, supporting 144Hz NVIDIA GeForce GTX 1650Ti with 4 GB GDDR6 memory with bundled monitor. mouse. kevboard and AVR Wireless Presenter System with Lavalier Microphone 5-Port Gigabit Unmanaged Desktop Switch 660 LED Bulb Panel 3200-5600K with 78.7 Inches Stand Lighting Kit High Speed HDMI™ Cable with Ethernet7.60m (25t1)4K@60Hz (4:2:0) 'Camera to AV Mixer/Media Box High Speed HDMI™ Cable with Ethernet10.70m (35t1)4K@60Hz (4:2:0) 'Interactive Display to AV Mixer/Media Box High-Speed HDMI Cable 0.90m (3f1)4K@60Hz (4:4:4) "AV Mixer/Media box to HDMI Capture Box Backdrop Setup Converter, HDMI (female) to Display Port 5 meters LAN Patch Cord Additional Specifications and Terms of Reference	77,000.00
1 Mobile Rack for 60-100 Tracking Camera 2 1/2.8-inch-high quality CMOS sensor. Resolution up to 1920x1080 1 Tripod System Kit Two-stage aluminum tripod with 60mm bowl, Supports loads up to 11 lb. Fixed pan/lilt drag with independent pan/lilt locks VP-CkB Keyboard Controller 1 Full function system keyboard controller for PTZ, conference and surveillance camera. With 4D stick, password protected HDMI Capture Box Max input resolution 1920x1200, with USB, 1HDMII, embedded audio Streaming PC 5.6" display with IPS and Full HD 1920 x 1080 resolution, supporting 144Hz NVIDIA GeForce GTX 1650Ti with 4 GB GDDR6 memory with bundled monitor. mouse, kevboard and AVR Wireless Presenter System with Lavalier Microphone 5-Port Gigabit Unmanaged Desktop Switch 660 LED Bulb Panel 3200-5600K with 78.7 Inches Stand Lighting Kit High Speed HDMI™ Cable with Ethernet7.60m (25ft)4K@60Hz (4:2:0) *Camera to AV Mixer/Media Box High—Speed HDMI™ Cable with Ethernet10.70m (35ft)4K@60Hz (4:2:0) *Interactive Display to AV Mixer/Media Box High—Speed HDMI Cable.90m (3ft)4K@60Hz (4:4:4) *AV Mixer/Media box to HDMI Capture Box Backdrop Setup Converter, HDMI (female) to Display Port 5 meters R66 Coaxial Cable with BNC Connector 2 meters 3.5mm XLR Female 5 meters LAN Patch Cord Additional Specifications and Terms of Reference	
1/2.8-inch-high quality CMOS sensor. Resolution up to 1920x1080 1 Tripod System Kit Two-stage aluminum tripod with 60mm bowl, Supports loads up to 11 lb, Fixed pan/tilt drag with independent pan/tilt locks VP-CKB Keyboard Controller 1 Full function system keyboard controller for PTZ, conference and surveillance camera. With 4D stick, password protected HDMI Capture Box Max input resolution 1920x1200, with USB, 1HDMI, embedded audio Streaming PC 5.6° display with IPS and Full HD 1920 x 1080 resolution, supporting 144Hz NVIDIA GeForce GTX 1650Ti with 4 GB GDDR6 memory with bundled monitor. mouse. kevboard and AVR Wireless Presenter System with Lavalier Microphone 1 5-Port Gigabit Unmanaged Desktop Switch 660 LED Bulb Panel 3200-5600K with 78.7 Inches Stand Lighting Kit High Speed HDMI™ Cable with Ethernet7.60m (25ft)4K@50Hz (4:2:0)  "Camera to AV Mixer/Media Box High Speed HDMI™ Cable with Ethernet10.70m (35ft)4K@60Hz (4:2:0) "Interactive Display to AV Mixer/Media Box High-Speed HDMI Cable0.90m (3ft)4K@60Hz (4:4:4) *AV Mixer/Media box to HDMI Capture Box Backdrop Setup 2 Converter, HDMI (female) to Display Port 5 meters RG6 Coaxial Cable with BNC Connector 2 meters 3.5mm XLR Female 5 meters LAN Patch Cord Additional Specifications and Terms of Reference	
1 Tripod System Kit Two-stage aluminum tripod with 60mm bowl, Supports loads up to 11 lb, Fixed pan/tilt drag with independent pan/tilt locks VP-CKB Keyboard Controller  1 Full function system keyboard controller for PTZ, conference and surveillance camera. With 4D stick, password protected HDMI Capture Box Max input resolution 1920x1200, with USB, 1HDMI, embedded audio Streaming PC 5.6° display with IPS and Full HD 1920 x 1080 resolution, supporting 144Hz NVIDIA GeForce GTX 1650Ti with 4 GB GDDR6 memory with bundled monitor. mouse. keyboard and AVR Wireless Presenter System with Lavalier Microphone  1 5-Port Gigabit Unmanaged Desktop Switch 660 LED Bulb Panel 3200-5600K with 78.7 Inches Stand Lighting Kit High Speed HDMI™ Cable with Ethernet7.60m (25ft)4K@60Hz (4:2:0)  *Camera to AV Mixer/Media Box High Speed HDMI™ Cable with Ethernet10.70m (35ft)4K@60Hz (4:2:0)  *Interactive Display to AV Mixer/Media Box High-Speed HDMI Cable with Ethernet10.70m (35ft)4K@60Hz (4:2:0)  *Interactive Display to AV Mixer/Media Box High-Speed HDMI Cable with BNC Connector 2 Converter, HDMI (female) to Display Port 5 meters RG6 Coaxial Cable with BNC Connector 2 meters 3.5mm XLR Female 5 meters LAN Patch Cord Additional Specifications and Terms of Reference	
VP-CKB Keyboard Controller Full function system keyboard controller for PTZ, conference and surveillance camera. With 4D stick, password protected HDMI Capture Box Max input resolution 1920x1200, with USB, 1HDMI, embedded audio Streaming PC 5.6" display with IPS and Full HD 1920 x 1080 resolution, supporting 144Hz NVIDIA GeForce GTX 1650Ti with 4 GB GDDR6 memory with bundled monitor. mouse, kevboard and AVR Wireless Presenter System with Lavalier Microphone 5-Port Gigabit Unmanaged Desktop Switch 660 LED Bulb Panel 3200-5600K with 78.7 Inches Stand Lighting Kit High Speed HDMI™ Cable with Ethernet7.60m (25ft)4K@60Hz (4:2:0) *Camera to AV Mixer/Media Box High Speed HDMI™ Cable with Ethernet10.70m (35ft)4K@60Hz (4:2:0) *Interactive Display to AV Mixer/Media Box High-Speed HDMI Cable0.90m (3ft)4K@60Hz (4:4:4) *AV Mixer/Media box to HDMI Capture Box Backdrop Setup Converter, HDMI (female) to Display Port 5 meters RG6 Coaxial Cable with BNC Connector 2 meters 3.5mm XLR Female 5 meters LAN Patch Cord Additional Specifications and Terms of Reference	
and surveillance camera. With 4D stick, password protected HDMI Capture Box Max input resolution 1920x1200, with USB, 1HDMI, embedded audio Streaming PC 5.6" display with IPS and Full HD 1920 x 1080 resolution, supporting 144Hz NVIDIA GeForce GTX 1650Ti with 4 GB GDDR6 memory with bundled monitor. mouse, kevboard and AVR Wireless Presenter System with Lavalier Microphone 5-Port Gigabit Unmanaged Desktop Switch 660 LED Bulb Panel 3200-5600K with 78.7 Inches Stand Lighting Kit High Speed HDMI™ Cable with Ethernet7.60m (25ft)4K@60Hz (4:2:0) "Camera to AV Mixer/Media Box High Speed HDMI™ Cable with Ethernet10.70m (35ft)4K@60Hz (4:2:0) "Interactive Display to AV Mixer/Media Box High—Speed HDMI Cable0.90m (3ft)4K@60Hz (4:4:4) *AV Mixer/Media box to HDMI Capture Box Backdrop Setup Converter, HDMI (female) to Display Port 5 meters RG6 Coaxial Cable with BNC Connector 2 meters 3.5mm XLR Female 5 meters LAN Patch Cord Additional Specifications and Terms of Reference	
Max input resolution 1920x1200, with USB, 1HDMI, embedded audio Streaming PC 5.6" display with IPS and Full HD 1920 x 1080 resolution, supporting 144Hz NVIDIA GeForce GTX 1650Ti with 4 GB GDDR6 memory with bundled monitor. mouse. kevboard and AVR Wireless Presenter System with Lavalier Microphone  1 5-Port Gigabit Unmanaged Desktop Switch 660 LED Bulb Panel 3200-5600K with 78.7 Inches Stand Lighting Kit High Speed HDMI™ Cable with Ethernet7.60m (25tf)4K@60Hz (4:2:0) *Camera to AV Mixer/Media Box High Speed HDMI™ Cable with Ethernet10.70m (35tf)4K@60Hz (4:2:0) *Interactive Display to AV Mixer/Media Box High—Speed HDMI Cable0.90m (3ff)4K@60Hz (4:4:4) *AV Mixer/Media box to HDMI Capture Box Backdrop Setup Converter, HDMI (female) to Display Port 5 meters RG6 Coaxial Cable with BNC Connector 2 meters 3.5mm XLR Female 5 meters LAN Patch Cord Additional Specifications and Terms of Reference	
supporting 144Hz NVIDIA GeForce GTX 1650Ti with 4 GB GDDR6 memory with bundled monitor, mouse, kevboard and AVR Wireless Presenter System with Lavalier Microphone  5-Port Gigabit Unmanaged Desktop Switch 660 LED Bulb Panel 3200-5600K with 78.7 Inches Stand Lighting Kit High Speed HDMI™ Cable with Ethernet7.60m (25ft)4K@60Hz (4:2:0) *Camera to AV Mixer/Media Box High Speed HDMI™ Cable with Ethernet10.70m (35ft)4K@60Hz (4:2:0) *Interactive Display to AV Mixer/Media Box High—Speed HDMI Cable0.90m (3ft)4K@60Hz (4:4:4) *AV Mixer/Media box to HDMI Capture Box Backdrop Setup  Converter, HDMI (female) to Display Port 5 meters RG6 Coaxial Cable with BNC Connector 2 meters 3.5mm XLR Female 5 meters LAN Patch Cord Additional Specifications and Terms of Reference	
Wireless Presenter System with Lavalier Microphone  5-Port Gigabit Unmanaged Desktop Switch  660 LED Bulb Panel 3200-5600K with  78.7 Inches Stand Lighting Kit High Speed HDMI™ Cable with Ethernet7.60m (25ft)4K@60Hz (4:2:0) *Camera to AV Mixer/Media Box High Speed HDMI™ Cable with Ethernet10.70m  (35ft)4K@60Hz (4:2:0) *Interactive Display to AV Mixer/Media Box High—Speed HDMI Cable0.90m (3ft)4K@60Hz (4:4:4) *AV Mixer/Media box to HDMI Capture Box Backdrop Setup  Converter, HDMI (female) to Display Port  5 meters RG6 Coaxial Cable with BNC Connector  2 meters 3.5mm XLR Female  5 meters LAN Patch Cord Additional Specifications and Terms of Reference	
3 660 LED Bulb Panel 3200-5600K with 78.7 Inches Stand Lighting Kit High Speed HDMI™ Cable with Ethernet7.60m (25ft)4K@60Hz (4:2:0) *Camera to AV Mixer/Media Box High Speed HDMI™ Cable with Ethernet10.70m (35ft)4K@60Hz (4:2:0) *Interactive Display to AV Mixer/Media Box High—Speed HDMI Cable0.90m (3ft)4K@60Hz (4:4:4) *AV Mixer/Media box to HDMI Capture Box Backdrop Setup Converter, HDMI (female) to Display Port Display Port Therefore The Mixer Reference  5 meters RG6 Coaxial Cable with BNC Connector Additional Specifications and Terms of Reference	
78.7 Inches Stand Lighting Kit High Speed HDMI™ Cable with Ethernet7.60m (25ft)4K@60Hz (4:2:0) *Camera to AV Mixer/Media Box High Speed HDMI™ Cable with Ethernet10.70m (35ft)4K@60Hz (4:2:0) *Interactive Display to AV Mixer/Media Box High—Speed HDMI Cable0.90m (3ft)4K@60Hz (4:4:4) *AV Mixer/Media box to HDMI Capture Box Backdrop Setup Converter, HDMI (female) to Display Port  meters RG6 Coaxial Cable with BNC Connector	
2 (35ft)4K@60Hz (4:2:0) *Interactive Display to AV Mixer/Media Box High—Speed HDMI Cable0.90m (3ft)4K@60Hz (4:4:4) *AV Mixer/Media box to HDMI Capture Box Backdrop Setup Converter, HDMI (female) to Display Port 5 meters RG6 Coaxial Cable with BNC Connector 2 meters 3.5mm XLR Female 5 meters LAN Patch Cord Additional Specifications and Terms of Reference	
High-Speed HDMI Cable0.90m (3ft)4K@60Hz (4:4:4) *AV Mixer/Media box to HDMI Capture Box Backdrop Setup Converter, HDMI (female) to Display Port 5 meters RG6 Coaxial Cable with BNC Connector 2 meters 3.5mm XLR Female 5 meters LAN Patch Cord Additional Specifications and Terms of Reference	
Converter, HDMI (female) to Display Port  5 meters RG6 Coaxial Cable with BNC Connector  2 meters 3.5mm XLR Female  5 meters LAN Patch Cord  Additional Specifications and Terms of Reference	
5 meters RG6 Coaxial Cable with BNC Connector 2 meters 3.5mm XLR Female 5 meters LAN Patch Cord Additional Specifications and Terms of Reference	
5 meters LAN Patch Cord Additional Specifications and Terms of Reference	
Additional Specifications and Terms of Reference	
************ Nothing Follows********  TOTAL ABC 23,32	3,329,030.0

1. All Entries must be typewritten

2. Delivery period within \_\_\_ \_calendar days 3. Warranty shall be for a period of six (6) months for supplies and materials, one (1) year for equipment from

date of acceptance by the procuring entity.

4. Price validity shall be for a period of \_\_\_ \_calendar days

5. G-EPS Registration Certificate shall be attached upon submission of the quotation.

6. Bidders shall submit original brochures showing

After having carefully read and accepted your General conditions, I / We quote on the item / s at prices noted above.

**Printed Name / Signature** 

certifications of the product being offered.

E-mail Address