

<div><div>BATAAN PENINSULA STATE UNIVERSITY</div><div>Balanga City, Bataan</div><div>OFFICIAL BIDDING FORM</div></div>						
Item No.	QTY	Unit	SPECIFICATIONS	OFFER; (Brand)	Unit Cost	Total Cost
1	1	Lot	Soil and Water Laboratory Instruments and Equipment			
			[6 UNITS] Prism Poles - 3 meters Pole Ø: 24mm/ 36mm/36mm Sections: 2 sections / 3 sections / 4 sections Full length: 2500mm / 3600mm / 5000mm Min. Length: 1370mm / 1550mm / 1700mm Lock Type: Twist			
			[2 UNITS] Leveling Rods Specifications Material: Aluminum Sections: 4m, 4 sections Overall length deviation: ±3mm Each meter deviation: ±0.5mm			
			[1 UNIT] DIGITAL PLANIMETER (Measuring range: Width 300mm maximum, Length free size, error of measurement: <±0.3%, Display: 6-digit LCD, Power: AC 220V 50Hz; DC7.2V)			
			[1 UNIT] TOTAL STATION SPECIFICATION (REFLECTORLESS) TELESCOPE Length: 154mm Objetive Lens Diameter- Telescope: 45mm Distance Meter 50mm Magnification: 30C Image: Erect Field of View: 1°30' Resolving Power: 3" Minimum Focus: 1.0m DISTANCE MEASUREMENT Single Prism: 4000m+1 Non-Prism: 400m+2 800m+ Accuracy : Prism Mode ± (2mm+2ppm x D)m.s.e. +3 Non-Prism Mode ± (3mm+2ppm x D)m.s.e. +3 Measuring Time Fine: 0.7s,Normal: 0.5s Fine: 0.3s, Normal: 0.2s+4 Meteorologic Correction: ATMOSense (Auto Sending) Prism Constant: Manual Input			
			ANGLE MEASUREMENT Method: Absolute Encoding Detecting System: H:2 sides, V: 2 Sides Min. Reading: 1''/5'' Accuracy: 2'' Diameter of Circle: 79mm Vertical Angle 0°: Zenith 0°/Horizontal:0° Unit: 360°/400gon/6400mil DISPLAY Display Unit: Graphic LCD 160 x 90 dots with white backlight No. of Unit: 2 Sides Keyboard: Alphanumeric Key TILT CORRECTION Tilt Sensor: Dual Axis Method: Liquid Electric Range: ±4' Setting Unit: 1'' LEVEL SENSITIVITY Plate level: 30''/2mm Circular level: 8'/2mm OPTICAL PLUMMET: (OPTIONAL: INTERNAL LASER PLUMMET) Image: Erect Magnification: 3X Focusing Range: 0.3m~∞ Field of view: 5°			
			DATA STORAGE & INTERFACE Internal Memory: >10,000 points or > 20, coordinates Data Interface: RS 232/SD-card/Mini-USB GENERAL Guide Light: YES Weight & Dimensions: 5.4kg, 340mm (H) X 160mm (W) X 150mm (L) Working Temperature: -20°C + 50°C Battery Type: Rechargeable Li-on Battery 3000mAh Battery Voltage: DC 7.4V Working Time: 16h PACKAGE INCLUSIONS Carrying case charger 2 battery multi port cable user manual plumb adjusting pin sd card mini USB cable screw driver wiping cloth laser receiver			

			iens cover rain cover carrying belt reflecting sheet warranty card transfer software CD			
			[2 UNITS] Atmometer/Evapotranspiration Simulator Specification: Accuracy: ±1% of evaporated water; Resolution: 0.01" reference evaporatranspiration Etr; Capacity: 12" Etr per filling; Temperature: 0-70°C max if using batteries; Humidity: 0-100%; Visual readings: sight tube with scale in inches and mm mounted on water reservoir; Output: Single pulse per 0.01" ETr; Output connection: Two wire, internal screw terminal block; Signal: Line pulled low for a 2.3 ±0.7 second pulse after each 0.01" ETr; Impedance: Normally open-circuit, 53 ohms during pulse; Transient protection: Fully lighting protected except direct strike to the unit; Power supply: Four alkaline "AA" cells (6V); External supply connection: 5 to 16 Vdc, 0.1A peak 0.4 mA average. Internal screw-terminal block; Mountings: Stainless steel vertical bracket; Material: Ceramic evaporation plate, green canvas plate cover, glass sight tube, PVC plastic housing, CMOS electronics; Size: 22.3" H x 3.1" Dia.; Weight Shipping: 3 lbs/4 lbs			
			[1 UNIT] GPS with 8 Megapixel Camera and BirdsEye Subscription Specifications: • Physical dimensions: 2.9" x 5.7" x 1.4" (7.48 x 14.42 x 3.64 cm) • Display size, WxH: 2"W x 3.5"H (5.06 x 8.93 cm); 4" diag (10.2 cm) • Display resolution, WxH : 272 x 480 pixels • Display type: bright, transfective 65k color TFT, dual-orientation touchscreen; sunlight readable • Touchscreen • Weight: 10.2 oz (289 g) with included lithium-ion battery pack; 11.7 oz (333 g) with 3 AA batteries (not included) • Battery: rechargeable lithium-ion (included) or 3 AA batteries (not included); NiMH or Lithium recommended • Battery life: up to 16 hours (lithium-ion); up to 22 hours (AA batteries) • Water rating: IPX7 • High-sensitivity receiver • Interface: high-speed USB and NMEA 0183 compatible • Camera: yes (8 megapixel with autofocus; automatic geo-tagging)			
			• Barometric altimeter • Electronic compass: Yes (tilt-compensated 3-axis) • Unit-to-unit transfer (shares data wirelessly with similar units) Maps & Memory • Basemap • Ability to add maps • Built-in memory: 4 GB • Accepts data cards: microSD™ card (not included) • Custom POIs (ability to add additional points of interest) • Waypoints/favorites/locations: 4000 • Routes: 200 • Track log: 10,000 points, 200 saved tracks Includes: • Montana 680 • Lithium-ion battery pack • USB cable • AC charger • Quickstart Guide			
2	1	Lot	Crop Processing Laboratory Instruments and Equipment			
			[2 UNITS] Sling Psychrometer specifications: 19.0 cm height x 2.5 cm width and 2.5 cm d; operating conditions = 25 to 120 degree fahrenheit and 10 to 100 % relative humidity			
			[1 UNIT] Compact Rice Mill Capacity (Hopper) = 250 grams paddy sample Capacity/Hr = 50kg/hr Power = 400W (0.5 HP) Single Phase Head Power = 1,900 RPM Follow Power = 1,000 RPM Size (LxWxH) = 700 x 340 x 1,000 (mm) Weight = 55 kg Rubber Size = Width of 35mm and diameter of 100mm Power Source = 220V, 60Hz			
3	1	Lot	Agricultural and Biosystems Engineering Machinery Equipment and Instruments			

			[12 SETS] MICROCONTROLLER STARTER KIT The package contains the following parts: 8pcs - 560 ohms resistors 1/4w 8pcs - RED 5mm LED 1pc - 10K potentiometer 1pc - 3 pins connector 4pcs - 2pins connector 8pcs - GREEN 5mm LED 1pc - CLEAR 5mm LED 1pc - 1N4002 DIODE 3pcs - 10K ohms resistor 1/4w 1pc - 2.2k ohms resistor 1pc - LDR 2pins 1pc - Dc motor 20pcs - Connecting wires 1pc - LM35 Temperature sensor or LM34 Temperature sensor 2pcs - Button Switch 1pc - relay 5V Ea2-4.5NU 1pc - gizDuino + ATmega644P 1pc - Solderless breadboard (ZY-60) 1pc - SG-90 Servo motor 1pc - transistor MPS2222A 1pc - 72LS595 Shift Register IC 1pc - 3pins connector 1pc - +5v Buzzer 1pc - 2x16 LCD			
			[12 SETS] UNIVERSAL MICRO CONTROLLER DIGITAL TRAINER'S KIT RS-232C I/F LCD port with 2x16 LCD display Realtime clock circuit Magnetic buzzer 2-digit 7-segment display 8-channel LED monitor Serial I1/O expander 4x3 keypad Encoder switch and push button switches 8-bit serial DAC 3x adjustable analog voltage sources & LM34 analog temperature sensor Relay and stepper motor driver Breadboard			
			[1UNIT] LATHE MACHINE Universal Precision lathe machine Three phase 220V60 hz Max swing overbed:400mm Center Distance: 1000mm Spindle bore: 52mm			
			*****nothing follows*****			

NOTE:

1. All Entries must be typewritten
2. Delivery period within _____ calendar days
3. Warranty shall be for a period of six (6) months for supplies and materials, one (1) year for equipment from date of acceptance by the procuring entity.
4. Price validity shall be for a period of _____ calendar days
5. G-EPS Registration Certificate shall be attached upon submission of the quotation.
6. Bidders shall submit original brochures showing certifications of the product being offered.

After having carefully read and accepted your General conditions, I / We quote on the item / s at prices noted above.

Printed Name / Signature

Tel. No. / Cellphone no.

E-mail Address